HDT STORAGE CONTAINERS with smooth or corrugated walls for storage and feeding of sowing machines or cleaning lines

4 standard- types Steel sheet S 235 JR	TYPE LC Flat bottom	TYPE SB Sloped bottom	TYPE TM Hopper bottom	TYPE TM-FK Hopper bottom
Walls: 2 mm thick	with/without outlet	with lateral outlet	with centric outlet	with centric outlet
Painting: RAL 6032	slider: 300x150mm	300x150mm	below: 120x120mm	below: 250x250mm
shining green	on 1 long side	wall inclination: 33°	wall inclination: 40°	wall inclination: 60°
Execution: smooth walls -painted/galvanized -stainless steel completely drainable (height up to 1,8m)				
standard d. (LxWxH)	1,50 x 1,20 x 1,34 m	1,50 x 1,20 x 1,34 m	1,50 x 1,20 x 1,34 m	1,5 x 1,2 x 1,34 m
volume	approx. 2,00 m ³	approx. 1,30 m ³	approx. 1,25 m ³	approx. 1,20 m ³
Execution: corrugated walls -painted/galvanized				
standard d. (LxWxH)	1,50 x 1,20 x 1,39 m			
volume	approx. 2,19 m ³	approx. 1,48 m ³	approx. 1,78 m ³	approx. 1,40 m ³

BENEFITS of HDT CONTAINERS :

- Very solid construction and execution
- > Forklift tracks on all 4 sides and openings for manual pallet truck on 2 sides
- > Convenient handling by: forklift, slewing ring or manual pallet truck
- High stackability
- Practical supplementary equipment, such as:
 Outlet spout with hose, aluminium cover easy to handle, PVC-covering sheet, heavy duty wheels, base frames with legs or wheels, etc.
- > Optional: special painting , food-safe painting, numbering
- Special execution accord. to customer's wishes, such as outlet on short side, container for washing of pumpkin seeds, container for collecting ash and dust, Big-Bag-bagging frames with container-bufferbin, feed stuff containers, etc.









art.no.	type	description	
GLC71.110	LC14-G	smooth walls, flat bottom without outlet, painted green or galvanized	
GLC71.111	LC14-S-G	smooth walls, flat bottom with lateral outlet, painted green or galvanized	
GLC71.220	SB14-G	smooth walls, sloped bottom with lateral outlet, painted green or galvanized	
GLC71.221	SB11-G	smooth walls, sloped bottom, lateral outlet, height 1 m, painted green or galvanized	
GLC71.330	TM14-G	smooth walls, hopper bottom with centric outlet, painted green or galvanized	
GLC71.440	TM14-FK-G	smooth walls, hopper bottom, centric larger outlet, 60° walls, painted or galvanized	
C71.110	LC14-P	corrugated walls, flat bottom without outlet, painted green or galvanized	
C71.111	LC14-S-P	corrugated walls, flat bottom with lateral outlet, painted green or galvanized	
C71.220	SB14-P	corrugated walls, sloped bottom with lateral outlet, painted green or galvanized	
C71.221	SB11-P	corrugated walls, sloped bottom, lateral outlet, height 1 m, painted or galvanized	
C71.330	TM14-P	corrugated walls, hopper bottom with centric outlet, painted green or galvanized	
C71.440	TM14-FK-P	corrugated walls, hopper bottom, centric larger outlet, 60° walls, painted/galvanized	
ST22	accessory	outlet spout for SB container, with hose 1 m and clamp	
ST33	accessory	outlet spout for TM container, without hose	
SL77	accessory	airmetal-hose 125 mm Ø with clamp, per metre	
D71-alu	accessory	alu-cover for all standard container types, weight 5,5 kg	
PV71.00	accessory	PVC-covering sheet, 650 g/m ² , with rubber cord, waterproof, hemmed	
R71.00	accessory	heavy duty wheels, castor and fixed wheels	
U716	accessory	base frame, height 600 mm, painted green or galvanized	
U711	accessory	base frame, height 1 m, painted green or galvanized	
A715	accessory	modular attachment, height 500 mm, painted green or galvanized	
A711	accessory	modular attachment, height 1 m, painted green or galvanized	

Application of containers in a processing line:



Marktstraße 24-26 – A-2004 Niederfellabrunn, AUSTRIA Tel.: 0043 2269 2287 – Fax: 0043 2269 24087 Email: office@hdt-foodmachines.at – Internet: www.hdt-foodmachines.at