HDT STORAGE CONTAINERS with smooth or corrugated walls for storage and feeding of sowing machines or cleaning lines

4 standard- types Steel sheet S 235 JR Walls: 2 mm thick Painting: RAL 6032 shining green	**TYPE LC** **Flat bottom** with/without outlet slider: 300x150mm on 1 long side	**TYPE SB** **Sloped bottom** with lateral outlet 300x150mm wall inclination: 33°	**TYPE TM** **Hopper bottom** with centred outlet below: 120x120mm wall inclination: 40°	**TYPE TM-FK** **Hopper bottom** with centred outlet below: 250x250mm wall inclination: 60°
Execution: **smooth walls** -painted/galvanized -stainless steel completely drainable (height up to 1,8m)				
standard d. (LxWxH)	1,50 x 1,20 x 1,34 m	1,50 x 1,20 x 1,34 m	1,50 x 1,20 x 1,34 m	1,5 x 1,2 x 1,34 m
volume	approx. 2,00 m³	approx. 1,25 m³	approx. 1,40 m³	approx. 1,20 m³
Execution: **corrugated walls** -painted/galvanized				
standard d. (LxWxH)	1,50 x 1,20 x 1,39 m	1,50 x 1,20 x 1,39 m	1,50 x 1,20 x 1,39 m	1,50 x 1,20 x 1,39 m
volume	approx. 2,19 m³	approx. 1,33 m³	approx. 1,49 m³	approx. 1,40 m³

BENEFITS of HDT CONTAINERS :

- **Very solid construction and execution**
- **Forklift tracks on all 4 sides and openings for manual pallet truck on 2 sides**
- **Convenient handling by: forklift, slewing ring or manual pallet truck**
- **High stackability**
- **Practical supplementary equipment, such as:**
  Outlet spout with hose, aluminium cover easy to handle, PVC-covering sheet, heavy duty wheels, base frames with legs or wheels, etc.
- **Optional: special painting , food-safe painting, numbering**
- **Special execution accord. to customer´s wishes, such as outlet on short side, container for washing of pumpkin seeds, container for collecting ash and dust, Big-Bag-bagging frames with container-bufferbin, feed stuff containers, etc.**









art.no.	type	description
GLC71.110	LC14-G	smooth walls, flat bottom without outlet, painted green or galvanized
GLC71.111	LC14-S-G	smooth walls, flat bottom with lateral outlet, painted green or galvanized
GLC71.220	SB14-G	smooth walls, sloped bottom with lateral outlet, painted green or galvanized
GLC71.221	SB11-G	smooth walls, sloped bottom, lateral outlet, height 1 m, painted green or galvanized
GLC71.330	TM14-G	smooth walls, hopper bottom with centred outlet, painted green or galvanized
GLC71.440	TM14-FK-G	smooth walls, hopper bottom, centred larger outlet, 60° walls, painted or galvanized
C71.110	LC14-P	corrugated walls, flat bottom without outlet, painted green or galvanized
C71.111	LC14-S-P	corrugated walls, flat bottom with lateral outlet, painted green or galvanized
C71.220	SB14-P	corrugated walls, sloped bottom with lateral outlet, painted green or galvanized
C71.221	SB11-P	corrugated walls, sloped bottom, lateral outlet, height 1 m, painted or galvanized
C71.330	TM14-P	corrugated walls, hopper bottom with centred outlet, painted green or galvanized
C71.440	TM14-FK-P	corrugated walls, hopper bottom, centred larger outlet, 60° walls, painted/galvanized
ST22	accessory	outlet spout for SB container, with hose 1 m and clamp
ST33	accessory	outlet spout for TM container, without hose
SL77	accessory	airmetal-hose 125 mm Ø with clamp, per metre
D71-alu	accessory	alu-cover for all standard container types, weight 5,5 kg
PV71.00	accessory	PVC-covering sheet, 650 g/m², with rubber cord, waterproof, hemmed
R71.00	accessory	heavy duty wheels, castor and fixed wheels
U716	accessory	base frame, height 600 mm, painted green or galvanized
U711	accessory	base frame, height 1 m, painted green or galvanized
A715	accessory	modular attachment, height 500 mm, painted green or galvanized
A711	accessory	modular attachment, height 1 m, painted green or galvanized

Application of containers in a processing line:



HDT
HAUS DER TECHNIK
Handelsgesellschaft m. b. H.

Kontakt: Fa. HDT – Haus der Technik GmbH
Marktstraße 24-26 – A-2004 Niederfellabrunn, AUSTRIA
Tel.: 0043 2269 2287 – Fax: 0043 2269 24087
Email: office@hdt-foodmachines.at – Internet: www.hdt-foodmachines.at